

EPISTAR

OSRAM

LED ВЛАГОЗАЩИТЕНО ИНДУСТРИАЛНО ТЯЛО / LITE 150 1500mm 40W


КОД: 651540DZEMXX ('XX' служи за индикация на цветна температура (CCT) 50=5000K)

WATERPROOF



5 ГОДИНИ
ГАРАНЦИЯ

gamma angles



cd/klm
C0 - C180
C90 - C270
 $\eta = 100\%$

IP RATE / 220V / 240V / MOUNT / CRI >80 / 120° / SMD 5730 / LIFE SPAN 80000 HOURS / GROUND

Технически показатели

Размер	SMD тип	Захранване	Захр. напрежение	Мощност	Цветна темп. CCT	IP защита	Свет. поток	CRI
1500mm	5730	Osram	220-240V	40W	3000K/4000K/5000K/6500K	IP65	5 920lm	CRI >80

Разсейвател	Ъгъл на изл.	Tc=C°	Стандарти	Апликация	PF	Авариен блок	Живот	Гаранция
PC/Опал	120°	-20°/+45°	ROHS / CE	ОТКРИТО/ ЗАКРИТО	PF>0.95	3h 5W	80.000h	2г. за авариен блок и 5г. за осветител



METAL SHEET

- DKP Metal Sheet
- White Paint
- 0,40 mm Thickness



CABLE GLAND

- Raw material : Polyamide
- Protection class: IP 65
- Heat Resistance : - 30 °C + 80 °C



CEILING CARRIER

- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,60 mm Thickness



MANDAL

- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,50 mm Thickness



DRIVER


- Suitable for CE and ROHS
- Criteria
- High Efficiency >90
- Harmonic Filter
- Lasts for 50.000 Hr





CABLE

- 0,80mm Thickness
- Electrolytic Solid Copper
- TI/PVC Isolation


ФОТОМЕТРИЧНИ ПОКАЗАТЕЛИ



Светлоразпределение при условен светлинен поток 1000lm



3D разпределение на светлинен поток



Спектър на светлинен поток 5000K