LED TRIPROOF INDUSTRAL FIXTURE / LITE 60 600mm 20W

CODE: 650620EDZXX ('XX' stand for CCT option 50=5000K)



Electrical Specification

Size	Light Source	Driver	Voltage	Power	CCT	IP Level	Lumens	CRI
600mm	2835	Osram	220-240V	20W	3000K/4000K/ 5000K/6500K	IP65	2 400lm	CRI >80

Diffuser	Angle	Tc=C°	Certificates	Application	PF	Directive	Lifespan	Warranty
PC/Opal	120°	-20°/+45°	ROHS / CE	OUTDOOR/ INDOOR	PF>0.95	LVD	50.000h	3 years

METAL SHEET
- DKP Metal Sheet
- White Paint
- 0,40 mm Thickness

CABLE GLAND
- Raw material : Polyamide
- Protection class: IP 65
- Heat Resistance : - 30 °C + 80 °C

CEILING CARRIER
- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,60 mm Thickness

MANDAL
- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,50 mm Thickness

DRIVER
- Suitable for CE and ROHS Criterias
- High Efficiency >%90
- Harmonic Filter
- Lasts for 50.000 Hr

CABLE
- 0,80mm Thickness
- Electrolytic Solid Copper
- TI/PVC Isolation

Test Reports



Luminaire light distribution of polar coordinates in the conditional flux 1000lm



Luminaire light distribution of the 3D



Spectrum of ligh 5000K