


LED TRIPROOF INDUSTRIAL FIXTURE / LITE 150 1500mm 50W

CODE: 651550EDZEMXX ('XX' stand for CCT option 50=5000K)

WATERPROOF

3 YEARS
WARRANTY

gamma angles


cd/klm
C0 - C180
C90 - C270
 $\eta = 100\%$

IP RATE
IP65
220V
240V
MOUNT
CRI
>80
120°
SMD
2835
LIFE SPAN
50000
HOURS
GROUND

Electrical Specification

Size	Light Source	Driver	Voltage	Power	CCT	IP Level	Lumens	CRI
1500mm	2835	Osram	220-240V	50W	3000K/4000K/ 5000K/6500K	IP65	7 100lm	CRI >80

Diffuser	Angle	Tc=C°	Certificates	Application	PF	Emergency Power	Lifespan	Warranty
PC/Opal	120°	-20°/+45°	ROHS / CE	OUTDOOR/ INDOOR	PF>0.95	3h 5W	50.000h	2y. for emergency unit 3y. for luminaire


METAL SHEET

- DKP Metal Sheet
- White Paint
- 0,40 mm Thickness


CABLE GLAND

- Raw material : Polyamide
- Protection class: IP 65
- Heat Resistance : - 30 °C + 80 °C


CEILING CARRIER

- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,60 mm Thickness


MANDAR

- Stainless Steel
- Easy and practical installation with biasing Feature
- 0,50 mm Thickness



DRIVER

- Suitable for CE and ROHS Criterias
- High Efficiency >%90
- Harmonic Filter
- Lasts for 50.000 Hr




CABLE

- 0,80mm Thickness
- Electrolytic Solid Copper
- Tl/PVC Isolation


Test Reports



Luminaire light distribution of polar coordinates in the conditional flux 1000lm



Luminaire light distribution of the 3D



Spectrum of light 5000K